

# ばね座金規格一覧

ばね座金の寸法								
呼び	内径		一般用(2号)			重荷重用(3号)		
			断面寸法(最小)		外径D (最大)	断面寸法(最小)		外径D (最大)
	基準寸法	許容差	幅 b	厚さ t		幅 b	厚さ t	
2	2.1	+0.25 0	0.9	0.5	4.4			
2.5	2.6	+0.3 0	1.0	0.6	5.2			
3	3.1		1.1	0.7	5.9			
(3.5)	3.6		1.2	0.8	6.6			
4	4.1	+0.4 0	1.4	1.0	7.6			
(4.5)	4.6		1.5	1.2	8.3			
5	5.1		1.7	1.3	9.2			
6	6.1		2.7	1.5	12.2	2.7	1.9	12.2
(7)	7.1	+0.5 0	2.8	1.6	13.4	2.8	2.0	13.4
8	8.2		3.2	2.0	15.4	3.3	2.5	15.6
10	10.2	+0.6 0	3.7	2.5	18.4	3.9	3.0	18.8
12	12.2		4.2	3.0	21.5	4.4	3.6	21.9
(14)	14.2	+0.8 0	4.7	3.5	24.5	4.8	4.2	24.7
16	16.2		5.2	4.0	28.0	5.3	4.8	28.2
(18)	18.2		5.7	4.6	31.0	5.9	5.4	31.4
20	20.2	+1.0 0	6.1	5.1	33.8	6.4	6.0	34.4
(22)	22.5		6.8	5.6	37.7	7.1	6.8	38.3
24	24.5	+1.2 0	7.1	5.9	40.3	7.6	7.2	41.3
(27)	27.5		7.9	6.8	45.3	8.6	8.3	46.7
30	30.5	+1.4 0	8.7	7.5	49.9			
(33)	33.5		9.5	8.2	54.7			
36	36.5		10.2	9.0	59.1			
(39)	39.5		10.7	9.5	63.1			

在庫につきましては弊社営業部までお問合せください。