

# 組込み用ばね座金規格一覧

## ばね座金の寸法

呼び	内径 d		2 号			3 号		
			断面寸法 (最小)		外径D (最大)	断面寸法 (最小)		外径D (最大)
	基準寸法	許容差	幅 b	厚さ t		幅 b	厚さ t	
2	1.71	+0.15 0	0.9	0.5	4.0			
2.3	2.02		1.0	0.6	4.5			
2.6	2.29		1.0	0.6	4.9			
3	2.65	+0.18 0	1.1	0.7	5.4			
(3.5)	3.08		1.2	0.8	6.1			
4	3.53	0	1.4	1.0	7.0			
(4.5)	4.05	+0.25 0	1.5	1.2	7.7			
5	4.50		1.7	1.3	8.5			
6	5.40	+0.3 0	2.7	1.5	11.4			
(7)	6.40		2.8	1.6	12.5			
8	7.30	+0.4 0	3.2	2.0	14.4	3.3	2.5	15.6
10	9.30		3.7	2.5	17.4	3.9	3.0	18.0
12	11.30		4.2	3.0	20.5			
(14)	13.40		4.7	3.5	23.5			
16	15.30		5.2	4.0	26.5			
(18)								
20								
(22)								
24								
(27)								
30								

在庫につきましては弊社営業部までお問合せ下さい。